

Default Models

Ryan Levy

Physics Department, University of Michigan, Ann Arbor, MI

Abstract

The Maxent method uses entropy S of a spectral function $A(\omega)$, defined with respect to an underlying default model $D(\omega)$ such that $S = - \int d\omega A(\omega) \ln \frac{A(\omega)}{D(\omega)}$. This document provides several plots of available default models for use in the Maxent program.

Contents


I	Flat	2
II	Gaussian	3
III	Lorentzian	7
IV	(Linear/Quadratic) Exponential Decay	8

Part I

Flat

DEFAULT_MODEL="flat"

Flat




Part II

Gaussian

DEFAULT_MODEL="gaussian"


SIGMA=--



DEFAULT_MODEL="shifted gaussian"

SIGMA=

SHIFT=




DEFAULT_MODEL="double gaussian"

SIGMA1=

SIGMA2=

Double Gaussian
 $\sigma_1=\sigma_2=1; \mu(\text{shift})=\pm 1$



DEFAULT_MODEL="Two gaussians"


SIGMA1=--

SIGMA2=--

SHIFT1=--

SHIFT2=--

NORM1=--




Part III

Lorentzian

DEFAULT_MODEL="Lorentzian"

GAMMA=--



See Gaussian for similar models (replace gaussian with lorentzian)


Part IV

(Linear/Quadratic) Exponential Decay

DEFAULT_MODEL="linear rise exp decay"

LAMBDA=--

Linear Rise Exponential Decay



DEFAULT_MODEL="quadratic rise exp decay"

LAMBDA=

